



Rec'd PCT APTO 18 MAY 2005  
1095355145/09/883



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

REC'D 26 MAR 2004

WIPO


PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed


*Stephen Hordley*

Dated 18 March 2004

**PRIORITY  
DOCUMENT**

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

**BEST AVAILABLE COPY**



30JAN04 1869269-6 000016  
P01/7700 0.00-0401927.9 CHEQUE

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

# Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference

NS/SD/04017

2. Patent application number

(The Patent Office will fill in this part)

0401927.9

20 JAN 2004

3. Full name, address and postcode of the or of each applicant (underline all surnames)

First Major Assets Limited,  
8 Kensington Palace Gardens  
London  
W8 4QP

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom

7772346002

4. Title of the invention

Resilient Cable Tidy

5. Name of your agent (if you have one)

BROOKES BATCHELLOR

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

102-108 Clerkenwell Road  
London EC1M 5SA

Patents ADP number (if you know it)

08142291001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number  
(if you know it)

Date of filing  
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing  
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if

Yes

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body.

See note (d))

# Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.  
Do not count copies of the same document

Continuation sheets of this form

Description 5

Claim(s) 3

Abstract 1

Drawing(s) 3 + 3

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

*Nigel Shindler*

29/1/04

12. Name and daytime telephone number of person to contact in the United Kingdom

Nigel Shindler 020 7253 1563

## Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

## Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

## CABLE TIDY

The present invention relates to a housing or receptacle for loose electrical cable.

5 In a typical office or home environment because of the large number of electrical and electronic appliances such as computers, TV, Hi Fi, etc which are to be connected to the mains, usually via a multiway adapter, there typically results an unsightly and possibly dangerous tangle of cables, which is difficult to control. Accordingly, the prior art such as WO/0041276 provides an arrangement which facilitates the control of such  
10 cables, and is very simple to put into effect, without requiring any specialised electrical equipment. However in prior art solutions there can be a problem that due mainly to inductive effects in the cable, in the absence of sufficient air circulation, a build up of heat may occur within the enclosure rendering the enclosure unsafe due to the possibility of insulation melting leading to short circuits and possible fire risk.

15

Accordingly the present invention provides a receptacle for electrical cable comprising a substantially rigid member carrying a flexible cable retaining member which is so formed as to allow a flow of air past the cable. The flexible member is preferably connected to the rigid member by relatively stiff but flexible straps which allow easy  
20 access to the interior of the receptacle and to further grip whilst helping to hold the cables securely in place. Preferably the cable retaining member has sufficient capacity to receive a multiway adapter as well as associated cables.

In a preferred embodiment the rigid member comprises a bent sheet which is  
25 preferably of plywood or moulded plastics, but metal or other rigid material may also be suitable. The flexible member preferably comprises an elasticated net. The net is preferably elastic enough to permit relatively bulky electrical plug appliances such as

mobile phone chargers to be pushed through the apertures of the net and held securely inside it. However, any flexible material with a sufficient number of apertures to allow heat to quickly dissipate from the cable is suitable for the flexible member. The straps are preferably elasticated, being expandable enough to facilitate easy removal of the net to add or remove cables and firm enough to secure the flexible member in place, although any flexible or non-flexible connecting material is suitable. In a preferred embodiment there are two exit means from the device whereby cable exits to the power supply through one exit means and to an appliance or appliances through the other exit means. Preferably, the rigid member is adapted to hang from a table, desk, shelf or the like or adapted to stand vertically to save space. The rigid member may have guide slots for the cables so as to hold them in place and improve the appearance.

Some embodiments of the invention will now be described, by way of example, with reference to the accompanying drawings, in which:

15

Figure 1 is a rear perspective view of a first embodiment of the invention in a first working orientation;

Figure 2 is a rear perspective view of the embodiment of Figure 1 in use;

Figure 3 is a further rear perspective view of the embodiment of Figure 1;

20 

Figure 4 is a front perspective view of the embodiment of Figure 1;

Figure 5 is a rear perspective view of the embodiment of Figure 1 in a second working orientation in conjunction with a table;

Figure 6 is a side view of the arrangement of Figure 5;

25 

Figure 7 is a similar view to that of Figure 5, but also shows the arrangement of cable in the device;

Figure 8 is a front perspective view of a second embodiment of the invention;

Figure 9 is a front perspective view of a third embodiment of the invention;

Figure 10 is a rear perspective view of a fourth embodiment of the invention in use;

Figure 11 is a perspective view of the fourth embodiment of the invention positioned to facilitate removal of wires;

Figure 12 is a perspective view of the fourth embodiment of the invention illustrating removal of the flexible member;

Figure 13 is a perspective view of the fourth embodiment of the invention with the flexible member removed; and

Figure 14 is a perspective view of the fourth embodiment of the invention with the wires removed.

10

Referring to the drawings, Figure 1 shows a first embodiment of the invention in a standing orientation, which comprises a rigid member 1 formed from a rectangular sheet of plywood bent to form a base 2 so that it can stand upright. A resilient, flexible cable-retaining member 3 comprises an elastic net and is attached to the rigid member 1 by a pair of elastic straps 4 and 5. The ends of the straps 4 and 5 are connected by screws or the like to the rigid member thus forming openings allowing the cables to be introduced between the net and the rigid member 1 as shown in Figure 2, and indicated by arrows 'A' in Figure 3. The rigid member 1 also includes cable guides which comprise slots 6 and 7 and a trough 8 which help to position and retain the cable. The base of the rigid member also has resilient strips of silicone or rubber 9 and 10 on its inner surface for use in an alternative working position, as explained below.

20

As an alternative, straps 4 and 5 need not be resilient but can be made from cord. As a further alternative, the flexible member need not be resilient but can be a string net or other net of non-resilient material.

25

Figures 5, 6 and 7 show the device of Figure 1 in the alternative working position, in which it is suspended on the edge of a table and is particularly useful as it takes up no space on the floor which in an office is often already crowded. As shown in Figure 6 the suspension is facilitated by the included angle  $\alpha$  being such that the centre of gravity of the device is inboard relative to the edge of the table. In addition, the resilient strips 9 and 10 on the base 2 increase the friction between the surface of the table and the base. As shown in Figure 7 the trough 8 is particularly useful in this second working position as, when some of the cable is resting within it, it reduces the force pulling the cable out of the flexible member 3.

10

The device can also be used in a third working position wherein the rigid member is positioned with the base 2 and the trough 8 resting on the floor such that the flexible member 3 hangs below the rigid member 1 and the rigid member 1 can be used as a footstool. This can provide a footrest under a desk whilst hiding the cable.

15

Figures 1 to 7 show the preferred form of cable management slots or guides 6 and 7 which extend inwards from the outer edges of the base 2 of the rigid member and then extend upwardly towards the flexible member 3. The benefit of this method of cable retention is that when the rigid member is being used in the "standing" position, once the cables are threaded through the guide they are located by three sides of the guide and retained in position by the supporting surface. In the second working position the guides 6 and 7 retain the cable between the sides of the guide and the adjacent surface of the table, shelf or desk.

20

25

Figure 8 shows a second embodiment of the invention having alternative guides 11 and 12 to retain the cable which comprise slots extending inwards from the outer edges of the rigid member. These slots are particularly useful when the device is in the upright

position as the cables can be introduced easily without having to slide them in a vertical direction.

Figure 9 shows a third embodiment of the invention this time with a different style of guide, in which slots 13 and 14 extend inwards from the outer edges of the rigid member and then (when the device is in an upright position) extend downwards in order to hold the cable more tightly. As will be clear from the drawing, the length of vertical extension of slots 13 and 14 can be varied depending on the degree of cable retention required. The lengths of the slots may be the same providing a more aesthetically pleasing symmetry, or may be different, allowing the user to choose the degree of cable retention. This style of guide is particularly useful if the cable tidy is used in different orientations.

Figure 10 shows a fourth embodiment wherein there is one continuous elasticated strap or surround around the flexible member. The strap is connected removably to the rigid member by studs with enlarged heads or the like, acting as hooks, thus forming openings allowing the cables to be introduced between the flexible and rigid members as illustrated in figures 10 and 11, and enabling the flexible member to be easily removed to access the cables or multi-way connectors as illustrated in figures 12-14.

In alternative arrangements, the flexible member and/or the strap may not be resilient but may be made from other materials as in the first embodiment. In further alternative arrangements, at least part of the flexible member or the strap is not removable, but remains attached while other parts are removed for access to the cables. In further alternative arrangements, there is more than one strap as in the first embodiment.



## Claims

1. A receptacle for electrical cable comprising a substantially rigid member carrying a flexible cable retaining member which is so formed as to allow a flow of air past the cable.  
5
2. A receptacle according to claim 1, wherein the flexible member is connected to the rigid member by at least one strap.
- 10 3. A receptacle according to claim 2, wherein said at least one strap is resilient.
4. A receptacle according to claim 2, wherein said at least one strap is elasticated.
5. A receptacle according to any preceding claim, wherein said flexible member is resilient.  
15
6. A receptacle according claim 2, wherein the flexible member is connected to the rigid member by one strap forming a border around the periphery of the flexible member.
- 20 7. A receptacle according to claim 2 wherein at least part of said at least one strap connects the flexible member to the rigid member removably.
8. A receptacle according to claim 7 wherein said at least one strap connects the flexible member to the rigid member removably via studs with enlarged heads acting as  
25 hooks.

9. A receptacle according to any preceding claim, wherein the flexible member is a perforated bag.

5 10. A receptacle according to any preceding claim, wherein the flexible member is a net.

11. A receptacle according to any preceding claim, wherein the flexible member is elasticated.

10 12. A receptacle according to claim 10 and claim 11, wherein the net is sufficiently elastic to permit an electrical plug appliance to be pushed through an aperture of the net and then retained securely inside it.

15 13. A receptacle according to any preceding claim in which the rigid member comprises a sheet of material, one edge of which is formed into an L-shaped cross-section, so as to form a stand.

14. A receptacle according to any one of the preceding claims, wherein the rigid member includes cable guide means.

20

15. A receptacle according to claim 14, wherein said guide means comprises slots for locating cables.

25 16. A receptacle according to claim 14 or claim 15, wherein said guide means includes a trough formed at the opposite edge to the edge having the L-shaped cross-section.

17. A receptacle according to claim 15, wherein the rigid member is formed from a sheet material and said each slot for locating cables extends inwards from an edge of the rigid member.

5 18. A receptacle according to claim 15, wherein said slots for locating cables are so shaped as to co-operate with an adjacent surface in order to retain the cables.

19. A receptacle according to claim 15, wherein said slots for locating cables are formed so as to co-operate with a table in order to retain the cables.

10

20. A receptacle according to any one of the preceding claims, wherein the rigid member is adapted to hang from the edge of a desk.

15 21. A receptacle according to any one of the preceding claims, wherein the rigid member is adapted to stand upright on a surface.

22. A receptacle according to any one of the preceding claims, wherein said rigid member has silicone or rubber strips to grip the surface of a table desk or the like.

20 23. A receptacle according to any one of the preceding claims which is also adapted to house a multiway connector.

24. A receptacle substantially as herein described with reference to Figures 1 to 14 of the accompanying drawings.

25

**Abstract**

A cable tidy, comprising a rigid support member, carrying a cable retaining net which allows air to flow past the cable in order that heat dissipates quickly.




Figure 4




Figure 1




Figure 3




Figure 5




Figure 2






Figure 7

Figure 6





your hand luggage under  
the supervision of you.

Renders of the cable tidy standing.  
Exploration of possible shapes for  
'cable management slots'.





figure 8

Figure 9



Single strips of silicone,  
or translucent rubber tubing  
forms a discrete double sided  
grip, and protection from scratches.




FIGURE 10




FIGURE 13




FIGURE 11




FIGURE 14




FIGURE 12

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**